

product data sheet

VARSYNTH ULTRA 5W/30

High Performance Low SAPS Synthetic Engine Oil

Varsynth Ultra 5w/30 is a Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 and 6 engines for normal and extended drain intervals.

Varsynth Ultra 5w/30 engine oil is for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 5 & 6 engines requiring Low SAPS engine oil.

Varsynth Ultra 5w/30 engine oil has been developed for GM Opel Euro 5 and 6 engines requiring GM Dexos 2 engine oil specification as well as other major engine manufacturers. The specification is particularly suited to vehicles equipped with anti-pollution systems such as diesel particulate filters where its low SAPS levels will greatly prolong the lifetime of the filter. It is also suitable for other types of diesel engines as well as petrol engines.

Features & Benefits

- ✚ Provides extended oil drain intervals and reduces maintenance costs
- ✚ Low SAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter
- ✚ Excellent engine cleanliness and wear protection increasing engine durability
- ✚ Excellent high and low temperature performance
- ✚ Reduces fuel consumption

Meets Manufacturers Performance & Recommendations of

Mercedes Benz	MB 229.52	ACEA	C2 suitable for
GM	Dexos 2	ACEA	C3
BMW	LL-04	API Petrol	SN
VW	502.00, 505.01	API Diesel	CF
Ford	M2C 917-A	Renault	RN0700/07100

Typical Inspection Data

Property	Unit	Inspection Data
Absolute Density, 15 °C	kg/m ³	853
Kinematic Viscosity, 40 °C	mm ² /s	68.6
Kinematic Viscosity, 100 °C	mm ² /s	11.8
Viscosity Index		165
Flash Point	°C	210
Pour Point	°C	- 32
Sulphated Ash Content	% mass	0.79